

DAS 4620

Slimline cooker hood  
with EasySwitch controls for convenient operation



- Classic design – stainless steel panel, 60 cm wide
- Unique user convenience – Con@ctivity
- LED strip for uniform lighting
- Efficient filtration- 10-ply stainless-steel grease filter
- Recirculation mode – Active AirClean or Longlife AirClean filter

EAN: 4002516495963 / article number: 28S4620SD / material number: 11862180

<b>Construction type</b>	
Slimline cooker hood	•
<b>Design</b>	
Colour	Stainless steel
<b>Operating modes</b>	
Type of air guide	Convertible
Recirculation conversion kit (order separately)	DUU 151
<b>User convenience</b>	
Networking with Miele@home	•
Automatic function Con@ctivity 3.0 (WiFi)	•
Electronic controls	•
Light-touch controls	•
Programmable Booster level switch-off	•
Run-on time 5 / 15 min.	•
Grease filter saturation indicator programmable	•
Active charcoal filter saturation indicator programmable	•
<b>Efficiency and sustainability</b>	
Annual energy consumption in kWh/year	23,1
ECO package	•
<b>Filter system</b>	
Number of dishwasher safe stainless steel grease filters	1
<b>Lighting</b>	
LED	•
Number x W	1 x 3 W
Light intensity in Lx	330
Colour temperature in K	3.500
Dimmer function	•
<b>Fan</b>	
Dual-action fan	•
ECO motor (DC motor)	•
<b>Air throughput with max. duct diameter in extraction mode (not for external version)</b>	
Air throughput in Level 1 (m <sup>3</sup> /h)	180
Air throughput in Level 2 (m <sup>3</sup> /h)	280
Air throughput in Level 3 (m <sup>3</sup> /h)	400
Air throughput in booster level 1 (m <sup>3</sup> /h)	600
Sound power in Level 1 (dB(A) re 1 pW)	38
Sound power in Level 2 (dB(A) re 1 pW)	48
Sound power in Level 3 (dB(A) re 1 pW)	56
Sound power in booster level 1 (dB(A) re 1 pW)	66
Sound pressure in Level 1 (dB(A) re 20 µPa)	25
Sound pressure in Level 2 (dB(A) re 20 µPa)	34
Sound pressure in Level 3 (dB(A) re 20 µPa)	42
Sound pressure in booster level 1 (dB(A) re 20 µPa)	53

DAS 4620

Slimline cooker hood  
with EasySwitch controls for convenient operation



<b>Air throughput in recirculation mode</b>	
Air throughput in Level 1 (m <sup>3</sup> /h)	165
Air throughput in Level 2 (m <sup>3</sup> /h)	265
Air throughput in Level 3 (m <sup>3</sup> /h)	380
Air throughput in booster level 1 (m <sup>3</sup> /h)	585
Sound power in Level 1 (dB(A) re 1 pW)	43
Sound power in Level 2 (dB(A) re 1 pW)	53
Sound power in Level 3 (dB(A) re 1 pW)	62
Sound power in booster level 1 (dB(A) re 1 pW)	72
Sound pressure in Level 1 (dB(A) re 20 µPa)	29
Sound pressure in Level 2 (dB(A) re 20 µPa)	40
Sound pressure in Level 3 (dB(A) re 20 µPa)	48
Sound power in booster level 1 (dB(A) re 1 pW)	59
<b>Safety</b>	
Safety switch-off	•
<b>Technical data</b>	
Canopy width in mm	596
Canopy height in mm	36
Canopy depth in mm	273
Minimum height above electric hobs in mm	450
Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
Net weight in kg	12,0
Length of supply lead in m	1,5
Standard plug fitted	•
Total rated load in kW	0,09
Voltage in V	230
Fuse rating in A	10
Frequency in Hz	50
Number of phases	1
<b>Installation notes</b>	
Extraction ducting connection at top	•
Diameter of extraction ducting connection in mm	150
<b>Standard accessories</b>	
Non-return flap	•

