

## DA 399-7 Classic

Wall mounted cooker hood  
with energy-efficient LED lighting and light-touch switches for easy use.



- Design - 898mm wide trapezoidal canopy
- Powerful - 500m<sup>3</sup>/h on the booster setting
- Efficient filtration- 10-ply stainless-steel grease filter
- Safe and easy to clean - Miele CleanCover
- For perfect functionality - accessories for proper venting

EAN: 4002515785881 / article number: 28399750D / material number: 10553480

Construction type	
Wall mounted cooker hood	•
Design	
Colour	Stainless steel
RAL colours available as customisation on request	•
Customisation possible on request	•
Variable height available as customisation on request	•
Operating modes	
Type of air guide	Convertible
Active charcoal filter (order separately)	DKF12-1
User convenience	
Electronic controls	•
Light-touch controls	•
Power levels (number without Booster level)	3
Booster level	•
Programmable Booster level switch-off	•
Cleaning convenience	
CleanCover	•
Efficiency and sustainability	
Annual energy consumption in kWh/year	58,9
Filter system	
Number of dishwasher-safe stainless steel grease filters	3
Lighting	
LED	•
Number x W	2 x 3 W
Light intensity in Lx	300
Colour temperature in K	3.000
Fan	
Dual-action fan	•
AC motor	•
Air throughput with max. duct diameter in extraction mode (not for external version)	
Air throughput in Level 1 (m <sup>3</sup> /h)	150
Air throughput in Level 2 (m <sup>3</sup> /h)	250
Air throughput in Level 3 (m <sup>3</sup> /h)	350
Air throughput in Booster level (m <sup>3</sup> /h)	500
Sound power in Level 1 (dB(A) re 1 pW)	41
Sound power in Level 2 (dB(A) re 1 pW)	47
Sound power in Level 3 (dB(A) re 1 pW)	55
Sound power in Booster level (dB(A) re 1 pW)	62
Sound pressure in Level 1 (dB(A) re 20 µPa)	26
Sound pressure in Level 2 (dB(A) re 20 µPa)	34
Sound pressure in Level 3 (dB(A) re 20 µPa)	40
Sound pressure in Booster level (dB(A) re 20 µPa)	47

## DA 399-7 Classic


Wall mounted cooker hood  
with energy-efficient LED lighting and light-touch switches for easy use.



Air throughput in recirculation mode	
Air throughput in Level 1 (m³/h)	100
Air throughput in Level 2 (m³/h)	150
Air throughput in Level 3 (m³/h)	250
Air throughput in Booster level (m³/h)	350
Sound power in Level 1 (dB(A) re 1 pW)	48
Sound power in Level 2 (dB(A) re 1 pW)	55
Sound power in Level 3 (dB(A) re 1 pW)	61
Sound power in Booster level (dB(A) re 1 pW)	68
Sound pressure in Level 1 (dB(A) re 20 µPa)	34
Sound pressure in Level 2 (dB(A) re 20 µPa)	41
Sound pressure in Level 3 (dB(A) re 20 µPa)	47
Sound power in Booster level (dB(A) re 1 pW)	53
Safety	
Safety switch-off	•
Technical data	
Overall height for extraction mode and external mode cooker hoods in mm	695
Overall height for recirculation mode cooker hoods in mm	825
Canopy width in mm	898
Canopy height in mm	120
Canopy depth in mm	520
Minimum height above electric hobs in mm	450
Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
Net weight in kg	26,0
Length of supply lead in m	1,5
Standard plug fitted	•
Total rated load in kW	0,13
Voltage in V	230
Fuse rating in A	10
Frequency in Hz	50
Number of phases	1
Installation notes	
Extraction ducting connection at top	•
Extraction connection at top and rear	•
Diameter of extraction ducting connection in mm	150
Telescopic chimney	•
Standard accessories	
Non-return flap	•
Adapter to reduce ducting diameter from 150 mm to 125 mm Ø	•

## DA 399-7 Classic

Wall mounted cooker hood  
with energy-efficient LED lighting and light-touch switches for easy use.



DA 399-6 (Installation drawing)

- 1) Extraction
- 2) Recirculation
- 3) Ventilation grille at top for recirculation
- 4+5) Installation cut-out (5 not required for recirculation)