

DA 6698 D Purist. Ed.6000

Island cooker hood with energy-efficient LED lighting and touch controls for simple operation.

Construction type



- Family design based on Miele builtin appliances
- Unique user convenience Con@ctivity
- Powerful 730m3/h on the booster setting
- Energy-efficient and quiet powerful ECO motor
- Pleasantly quiet Miele Silence package

Construction type	
Island cooker hood	•
Design	
Colour	Stainless steel
RAL colours available as customisation on request	•
Customisation possible on request	•
Variable height available as customisation on request	•
Operating modes	
Type of air guide	Convertible
Active charcoal filter (order separately)	DKF12-1
User convenience	
Electronic controls	•
Touch-on-glass controls	•
Miele@mobile app	. •
Power levels (number without Booster level)	3
Booster level	•
Programmable Booster level switch-off	•
Run-on time 5 / 15 min.	•
Grease filter saturation indicator programmable	•
Active charcoal filter saturation indicator programmable	•
Silence package	•
Cleaning convenience	
CleanCover	•
Efficiency and sustainability	
Annual energy consumption in kWh/year	32,1
PowerManagement system	•
ECO package	•
Appliance networking	
Miele@home	•
WiFiConn@ct	•
MobileControl	•
ShopConn@ct	•
Automatic function Con@ctivity 3.0 (WiFi)	•
Filter system	
Number of dishwasher-safe stainless steel grease filters	3
Lighting	
LED	•
Number x W	4 x 3 W

820

3.500

EAN: 4002515937006 / article number: 28669855D / material number: 10750490

Light intensity in Lx

Dimmer function

Dual-action fan
ECO motor (DC motor)

Fan

Colour temperature in K



DA 6698 D Purist. Ed.6000

Island cooker hood with energy-efficient LED lighting and touch controls for simple operation.




ind todori controls for simple operation.	
Air throughput with max. duct diameter in extraction mode (not for external version)	
Air throughput in Level 1 (m ³ /h)	200
Air throughput in Level 2 (m ³ /h)	320
Air throughput in Level 3 (m ³ /h)	450
Air throughput in Booster level (m³/h)	730
Sound power in Level 1 (dB(A) re 1 pW)	35
Sound power in Level 2 (dB(A) re 1 pW)	44
Sound power in Level 3 (dB(A) re 1 pW)	53
Sound power in Booster level (dB(A) re 1 pW)	65
Sound pressure in Level 1 (dB(A) re 20 µPa)	20
Sound pressure in Level 2 (dB(A) re 20 µPa)	29
Sound pressure in Level 3 (dB(A) re 20 µPa)	38
Sound pressure in Booster level (dB(A) re 20 µPa)	50
Air throughput in recirculation mode	
Air throughput in Level 1 (m³/h)	115
Air throughput in Level 2 (m ³ /h)	210
Air throughput in Level 3 (m³/h)	330
Air throughput in Booster level (m³/h)	480
Sound power in Level 1 (dB(A) re 1 pW)	45
Sound power in Level 2 (dB(A) re 1 pW)	55
Sound power in Level 3 (dB(A) re 1 pW)	64
Sound power in Booster level (dB(A) re 1 pW)	73
Sound pressure in Level 1 (dB(A) re 20 µPa)	30
Sound pressure in Level 2 (dB(A) re 20 µPa)	40
Sound pressure in Level 3 (dB(A) re 20 µPa)	49
Sound power in Booster level (dB(A) re 1 pW)	58
Safety	
Safety switch-off	•
Single pane tempered glass	•
Technical data	
Overall height for extraction mode and external mode cooker hoods in mm	705
Overall height for recirculation mode cooker hoods in mm	765
Canopy width in mm	898
Canopy height in mm	85
Canopy depth in mm	598
Minimum height above electric hobs in mm	450
Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
Net weight in kg	35,0
Hard-wired connection	
Total rated load in kW	0,12
Voltage in V	230
Fuse rating in A	10
Frequency in Hz	50
Number of phases	1
Installation notes	ı İ
Extraction ducting connection at top	•
Diameter of extraction ducting connection in mm	150
Telescopic chimney	•
Standard accessories	
Non-return flap	•



DA 6698 D Purist. Ed.6000

Island cooker hood with energy-efficient LED lighting and touch controls for simple operation.





DA 6698 D, CLST (Installation drawing)

- 1) Extraction cut-out
 2) Extraction
 3) Recirculation
 4) Installation option with spacer frame
 5) Ventilation grille at the top for recirculation
 6) A mains cable and, for extraction mode, flexible exhaust ducting is required from the ceiling connection to the connection on the cooker hood.