

KM 7404 FX

Induction hob with onset controls
with PowerFlex cooking area for maximum power output




- Quick selection via numerical keybank – ComfortSelect
- 4 cooking zones incl. 1 high-power PowerFlex cooking area
- A width of 592mm for flush-fit installation
- Shortest heating-up times - TwinBooster
- Communication with the hood - automatic function Con@ctivity

EAN: 4002516148876 / article number: 26740460D / material number: 11128630

Heating type	
Heating type	Induction
Construction type	
Independent of cooker	•
Design	
Elegant glass ceramic surface	•
Ceramic surface colour	Black
Flush-fit installation	•
Cooking zone details	
Number of cooking zones	4
Number of cooking areas	1
Maximum number of pans	4
PowerFlex cooking zone	
No.	2
Size in mm	150x230
Max. rating in W	2.100
Max. Booster power rating in W	3.000
Max. TwinBooster power rating in W	3650
Cooking zone	
Position	front left
Type	Dual-circuit ring
Size in mm	Ø 140-190
Max. rating in W	1850
Max. Booster power rating in W	2500
Max. TwinBooster power rating in W	3000
Position	rear left
Type	Dual-circuit ring
Size in mm	Ø 100-160
Max. rating in W	1400
Max. Booster power rating in W	1700
Max. TwinBooster power rating in W	2200
Position	right
Type	PowerFlex bridge
Size in mm	230x390
Max. rating in W	3400
Max. Booster power rating in W	4800
Max. TwinBooster power rating in W	7300
User convenience	
Display colour	Yellow
Permanent pan recognition	•
Pan and pan size recognition	•
Stop & Go function	•
Recall function	•
Minute minder	•
Safety switch-off	•
Auto heat-up	•
Keeping warm	•
Individual setting options (e.g. buzzers)	•

KM 7404 FX



Induction hob with onset controls
with PowerFlex cooking area for maximum power output



Appliance networking	
Miele@home	•
WiFiConn@ct	•
Automatic function Con@ctivity 3.0	•
Cleaning convenience	
Easy to clean ceramic glass	•
Safety	
Safety switch-off	•
Lock function	•
System lock	•
Integrated cooling fan	•
Overheating protection	•
Residual heat indicator	•
Technical data	
Dimensions in mm (width)	592
Dimensions in mm (height)	51
Dimensions in mm (depth)	492
Casing height incl. connection box in mm	51
Internal cutout dimensions in mm (width) with flush installation	570
Internal cutout dimensions in mm (depth) with flush installation	470
External cutout dimensions in mm (width) with flush installation	596
External cutout dimensions in mm (depth) with flush installation	496
Weight in kg	11
Total rated load in kW	7,300
Voltage in V	230
Frequency in Hz	50-60
Connection cable length in m	1,4
Standard accessories	
Mains cable	•

KM 7404 FX

Induction hob with onset controls
with PowerFlex cooking area for maximum power output



KM 7404 FX (installation drawing)

- 1) Front
- 2) Mains connection box. Mains connection cable L = 1440 mm
- 3) Stepped cut-out natural stone worktops
- 4) Wooden frame 13 mm (not includes)